



**Square Telescopic Columns for Series  
BC200, BCE300 and 80800  
high performance bag closing machines**

● **STURDY**

● **RELIABLE**

● **EFFICIENT**

## Square Telescopic Columns (without sewing machine and conveyor)

### Common Specification:

Range of height adjustment 750 - 1450 mm from lower edge of column to needle, 350 mm infinitely variable range by handle and 350 mm assembling range variable in seven steps of 50 mm each.  
Standard voltage for brake motors: 220-240, 380-415V, 3 phase, 50 Hz / 243-277, 420-480V, 3 phase, 60 Hz.  
Standard control voltage: 24V DC. Degree of protection: IP 55. Insulation class: F.  
Extra charge for other voltage and frequencies.  
Voltage for gear motor with frequency converter (feed-in device): 230 V, 50 / 60 Hz.  
Painting: RAL 9002, powder coated.

| Columns | For Machines | For Machines | Description |
|---------|--------------|--------------|-------------|
|---------|--------------|--------------|-------------|

### Single-head columns, manually height adjustable

|                  |   |                                       |  |
|------------------|---|---------------------------------------|--|
| <b>20600BEBC</b> | BC211/BCE311P01-1NW<br>BC291/BCE391P01-1NW                          | 80800CN<br>80800DN                    | With simplified electrical equipment, motor, motor protection switch and foot switch |
| 29926CB          |   |                                       | Conveyor controls with foot switch   |
| <b>20600EEBC</b> | BC211/BCE311P01-1NW<br>BC291/BCE391P01-1NW                          | 80800CN<br>80800DN                    | With control box, motor and foot switch  |
| 29926CE          |   |                                       | Conveyor controls with foot switch   |
| <b>20600FEBC</b> | BC211/BCE311P16-1M<br>BC211U24-1M<br>BC211PD26-2M                   | 80800RLMN<br>80800ULMN<br>80800TLMN   | With control box, filter regulator kit 29916PP and brake motor                       |
| 29926CM          |   |                                       | Conveyor controls with foot switch   |
| <b>20600HEBC</b> | BC211/BCE311P16-1M<br>BC211UA24-1M<br>BCE311KA12-1M<br>BC211PD26-2M | 80800RLMN<br>80800UALMN<br>80800TALMN | With control box for feed-in device, filter regulator kit 29916PP and brake motor    |
| 29926CM          |   |                                       | Conveyor controls with foot switch   |

### Accessories for Columns

|           |  |  |  |
|-----------|--|--|--|
| 20401F    |  |  | Movable base   |
| 20401M    |  |  | Stationary base  |
| 93065BF   |  |  | Kit of parts for filler cord<br>Two kits required on double-head columns |
| 998M28ABC |  |  | Thread break detector for series BC200, BCE300                           |
| 998M28A   |  |  | Thread break detector for series 80800                                   |
|           |  |  | On double-head columns two thread break detectors are required           |

Also available are bag **feed-in devices 29900** for easy handling as well as **belt- and slat-type conveyors 91605**.

Subject to change without notice © Union Special GmbH