



**SINGLE-NEEDLE, SINGLE-THREAD CHAINSTITCH OR TWO-THREAD DOUBLE LOCKED STITCH MACHINE WITH TOP AND BOTTOM FEED FOR USE IN AUTOMATED SYSTEMS**



101 SSa-1



401 SSa-1

**56100RBTA**

Single-needle, single-thread chainstitch machine (101) with top and bottom feed for seaming heavy weight as well as coated bags and simultaneously attaching a binding tape and "Easy-Open" tape (10 mm) from the top. Presser foot with guide for filler cord and one "Easy-Open" tape. Without binding tape folder.

Note: Sewing only in connection with tape resp. filler cord, end-chaining not possible.

**56100SABTA**

Single-needle, two-thread double locked stitch machine (401) with new improved thread take up, which eliminates thread wrapping around the main shaft.

Note: Sewing without tape, end-chaining possible.

Attention: All machine types will be delivered without thread stand.

Max. Speed:	4300 stitches / min. (depending on material and operation)
Stitch Range:	3.6 to 8.5 mm
Sewing Capacity:	6.0 mm
Seam Specification 56100RBTA:	101 SSa-1
Seam Specification 56100SABTA:	401 SSa-1
Standard Needle:	143GS200/080

Subject to change without notice © Union Special GmbH

