

**TWO NEEDLE DOUBLE LOCKED STITCH MACHINE WITH TOP AND BOTTOM FEED FOR EFFECTIVELY MANUFACTURING BAGS. FOR USE IN AUTOMATED SYSTEMS.**



(401.401) SSa-2

**56100SABT2A**

Two needle double locked stitch machine with top and bottom feed for seaming heavy weight coated and also uncoated bags. With new designed feed drive for faster speed, new improved thread take up, which eliminates thread wrapping around the main shaft. Left main shaft bushing with needle bearing. Automatic lubrication system, with advanced filtered oil return pump.

For use in automated systems.

Attention: This machine type will be delivered without thread stand.

Max. Speed: 4300 stitches/min. (depending on material and operation)  
Stitch Range: 3.6 to 8.5 mm  
Needle Distance: 6.4 mm  
Sewing Capacity: 6.0 mm  
Seam Specification: (401.401) SSa-2  
Standard Needle: 143GS200/080

Subject to change without notice © Union Special GmbH

Union Special LLC  
One Union Special Plaza  
Huntley, IL 60142, USA  
Phone: 847/669 4500,  
Fax: 847/669 4239  
www.unionspecial.com



Union Special GmbH  
Raiffeisenstraße 3  
71696 Möglingen, Germany  
Tel: +49 (0)7141/247-0,  
Fax: +49 (0)7141/247-100  
www.union-special.com

02-21\_en