

SINGLE NEEDLE DOUBLE LOCKED STITCH MACHINE FOR EFFECTIVELY MANUFACTURING CONTAINER BAGS

SEWING PARTS WITH SPECIAL RUST PREVENTION COATING



80800CNH

80800CDNH

with
**Pedestal PN382A862L or
Pedestal PN382G132 or
Sewing Table UN382G132**

- **STURDY**
- **EFFICIENT**
- **RELIABLE**
- **FAST**



SINGLE NEEDLE DOUBLE LOCKED STITCH MACHINE SEWING PARTS WITH RUST PREVENTION COATING

STITCH RANGE:	6.5 to 11 mm
STANDARD SETTING:	10 mm
SEWING CAPACITY:	up to 17 mm
STANDARD NEEDLE:	9848G 250/100
THREADS:	two, 2500 Denier (sewn off)
MAXIMUM SPEED:	1800 RPM (depending on sewing operation)
SEAM SPECIFICATION:	401 SSa-1 (80800CNH) 401.401 SSa-2 (80800CDNH)

Machine Style	Description	Application	Threads for Needle and Looper	Required Installation
80800CNH	<p>Single needle double locked stitch machine <u>with special rust prevention coating.</u> With built-in thread chain cutter and plain feed.</p> <p>Guide for filler cord from the top for sealing the needle punctures.</p> <p>Throat plate 80724C with guide for filler cord from below as an extra send and charge item.</p>	<p>For attaching filling and discharging tubes on CONTAINER BAGS.</p> <p>Crossing heavy seams is not possible.</p> <p>With electronic drives only: Stops adjustable in needle up and down position with simultaneously lifting the presser foot.</p>	Polypropylene thread 1000 to 4000 Denier	<p>PN382A862L Pedestal with clutchless electronic drive. Electro-pneumatic presser foot lifter.</p> <p>PN382G132 Pedestal with clutch motor (no automatic needle positioning). Mechanical presser foot lifter, foot treadle operated</p>
80800CDNH	<p>Same as 80800CNH, but two needle independent rows double locked stitch machine <u>with special rust prevention coating.</u> With built-in thread chain cutter and plain feed.</p> <p>Guide for filler cord from the top for sealing the needle punctures.</p> <p>Throat plate 80724CD with guide for filler cord from below as an extra send and charge item.</p>			<p>UN382G132 Sewing table with clutch motor (no automatic needle positioning). Mechanical presser foot lifter, foot treadle operated.</p>

Subject to change without notice © Union Special GmbH

