

Automatic High Performance Bag Closing Machine

*Sewing parts with special Ticarbo coating
for harshest conditions*

Coming soon



Features:

- *Sewing parts with special Ticarbo coating for better protection against rust*
- Optimized feeding through wider parts
- Independently adjustable chaining and presser foot pressure for improved bag feeding
- Individual control through your electronic devices
- Longer part life due to closed oil system
- Easy and quick sewing speed adjustment
- Easy setting of loose or tight seam as needed
- Simplified maintenance

BC211UA23-1NWT:

Two thread double locked chainstitch bag closing machine (stitch type 401) for closing filled bags respectively binding the seam with a folded crepe paper or PP-tape (Without tape folder). Presser foot bottom with guide for „Easy-Open“ tape.

Technical data:

- Start-Stop controlled by photocell
- Tape respectively thread chain with or without filler cord are automatically trimmed by a pneumatically operated guillotine cutter (actuated by rotary air cylinder)
- For application with bag feed-in, trimming and taping device with tape FolderTape width: 50, 60 (standard) 70 or 75 mm. Please specify when ordering
- Stitch length easily adjustable from 6.5 to 12.5 mm (2-4 SPI), standard setting 9 mm (3 SPI)
- Capacity under presser foot: up to 12.7 mm underneath tape cutter
- Sewing capacity on paper: up to 32 plies depending on weight of paper
- Sewing machine pitch pulley for adjusting speed of machine, working diameter from 90 mm (3 1/2 inch) to 108 mm (4 1/4 inch)
- Max. speed: up to 2750 RPM, depending on stitch length, operation and material

Application fields:

Special version for application in erosive environment caused by acids, lye etc. (e.g. fertilizers).

Subject to change without notice © Union Special GmbH

