


IMPROVED ECONOMY LINE

with rust protected parts

Introducing the better choice...





. . . in bag closing

BCE311PD26-2M

BCE311PD26-2M: Improved "ECONOMY" two needle independent row double locked chainstitch bag closing machine in automatic version for closing filled bags.

Internal forced lubrication system in closed shell design casting. Low noise and vibration.

Needle distance: 7.2 mm (Needles are staggered, front needle below) Start-Stop: automatically by feeler controlled proximity switch

Control voltage: 24 V DC

Thread chain trimming: automatically by an "advanced "electro-pneumatically operated guillotine

(Actuated by double acting air cylinder, see picture detail)

Fixed pitch pulley: working diameter of 108 mm (4 1/4 inch)

Maximum speed: up to 2000 stitches / min., depending on material and sewing operation

Stitch type: (401.401) Capacity under guillotine: 9.5 mm

Stitch length: 6.5 -11.5 mm, standard setting 10 mm

Sewing capacity on

paper bags: up to 32 plies of paper depending on weight of paper

Benefits:

- Improved needle thread take up control
- Independently adjustable chaining and pressure foot pressure for optimized bag feeding
- Protection against rust.
- High production: up to 20 bags per minute with a linear sewing speed up to 16 m/min. depending on stitch length, operation and material.
- Longer part life
- Easily set a loose or tight seam as needed
- Simplified maintenance

Subject to change without notice © Union Special GmbH

Union Special LLC One Union Special Plaza Huntley, IL 60142, USA Phone: 847/669 4500, Fax: 847/669 4239 www.unionspecial.com



Union Special GmbH 08-22_en Raiffeisenstraße 3 71696 Möglingen / Germany

Tel.: +49 (0)7141/247-0, Fax: +49 (0)7141/247-100 www.union-special.com